



## NAGMAN MOBILE CALIBRATION UNITS

### Typical Configuration of Modules

#### Electrical & Electronics – Mobical EE

- ✓ Function Generator
- ✓ 5½ digit Digital Multimeter
- ✓ Multifunction Calibrator
- ✓ Decade Resistance Box
- ✓ Variable AC & DC (Programmable) Power Supplies
- ✓ Power Supply for Unit Under Test



#### Pressure & Temperature – Mobical PT

- ✓ Pressure Indicator: Pneumatic -0.85 to 25 Bar; Hydraulic Upto 350 Bar
- ✓ Built-in / External Hand Pumps
- ✓ Dual Dry Block Temperature Calibrators
- ✓ Range: -35 from Ambient to 123°C & 50 to 350°C
- ✓ Multifunction Calibration & Power Supply for Unit Under Test

#### MOBICAL PTES (ELECTRICAL, ELECTRONICS, PRESSURE & TEMPERATURE)

### Multi-parameter Trainer

- ✓ Dry Block Temperature Calibrators (2 Nos.)
- ✓ Range : -35 from Ambient to 123°C & 50 to 350°C
- ✓ Function Generator
- ✓ 5½ digit Digital Multimeter
- ✓ Process (Multifunction) Calibrator
- ✓ Decade Resistance Box
- ✓ Variable AC & DC Power Supply for Units Under Test
- ✓ Integrated / Interfaced with CPU & foldable Touch Screen Monitor,
- ✓ CALMAN Plus – Calibration Management Software for Automatic / Semi-Automatic Test / Calibration routines; Data Collection / Storage etc.



Temperature, Pressure, and/or Electrical & Electronics Modules mounted in a rack, placed inside Mobile (sturdy) Trolley case, ready for use as Table-top Unit or for Field/Site Calibration.